



# Rotary Tiller

## Фреза почвообрабатывающая

Rotary Tiller is a secondary soil tillage machine which is powered by the power-take off drive of the tractor and easily attached to the tractor by its three point hitch and used generally in fields, orchards and vineyards for seed bed preparation, stubble ploughing and incorporation of organic materials into the soil. This machine is more economical in power, time and fuel because the motion is transferred from PTO by a gear system instead of chain system. The shafts of our machines are equipped with safety brake lining so that it prevents giving damage to the machines by squeezed stones and foots.

Фреза почвообрабатывающая предназначена для рыхления почвы без оборота пласта по фону зяби или весновспашки. Фреза за один проход выполняет следующие технологические операции: фрезерование почвы активными рабочими органами, уничтожение сорной растительности и выравнивание микрорельефа. Производится с шириной захвата до 3 м.

MODEL	Модель			AGRT 130	AGRT 160	AGRT 185	AGRT 210	AGRT 240
Number of Blade	количество ножей	pcs	шт	30	36	42	48	54
Total Lenght (A)	длина (A)	cm		150	174	198	223	254
Total Width (B)	ширина (B)	cm		70	70	70	70	70
Total height (C)	высота (C)	cm		120	120	120	120	120
Working Depth	глубина обработки	cm		22/9	22/9	22/9	22/9	22/9
Working Width	ширина захвата	cm		135	160	185	210	240
Required Power	мощность	hp	лс	50	55	60	65	70
Total Weight	масса	kg	кг	390	410	505	540	750

