

TRAILED ATOMIZER



- Draining system that quickly drains the water remaining in the tank after spraying
- Fast filling
- Control that provides homogeneous and precise spraying norm
- Spraying pump with 4 membranes having the best performance
- Filter system with check valve that can be cleaned easily
- Durable wheels that can operate in all kinds of field conditions
- Pressure filter that increases spraying efficiency by filtering pressurized water
- Stop lamps that ensure safety of the machine in traffic
- Atomizer nozzle with adjustable spray angle and drop stopping feature
- Fan protection wire designed to prevent possible accidents
- Drawbar that has height adjustment and can be attached to the tractor easily

SPECIFICATIONS (unit)	Material Of Tank	Capacity of Tank (lt)	Pump Model (Piston membrane)	Pump Flow (lt/min)	Pump Pressure (Bar)	Control Panel	Nozzle Type	Number of Nozzle (Psc)	Fan Diameter (cm)	Working Width (cm)	Required Tractor Power (BG)	Operating Speed (R/min)	Air Flow Rate (m3/h)	Weight (kg)	Width (cm)	Lenght (cm)	Height (cm)
FICUS F 1000	Polyester	1000	C 145	145	50	OTR 17	Brass Stopper Turbo	16	85	20-24	70	540	66000	516	168	365	135
FICUS F 1600	Polyester	1600	C 145	145	50	OTR 17	Brass Stopper Turbo	16	90	20-24	70	540	66000	550	178	365	135
FICUS F 2000	Polyester	2000	C 145	145	50	OTR 17	Brass Stopper Turbo	16	90	20-24	70	540	66000	550	180	410	135